

SPECIFICATION

| | |
|--|---|
| Model Name | GT-S |
| Case Type | Full Tower |
| Steel Thickness | 1.2mm |
| Motherboards | FLEX ATX / Micro ATX / ATX / MINI ATX / SSI CEB / SSI EEB(EATX) / XL-ATX |
| Case Dimensions | 251 x 630 x 563mm (W x H x D, overall) |
| Drive Bays | 5 x 5.25" (Exposed) / 7 x 3.5" HDD or 2.5" HDD (Internal) |
| Expansion Slots | 10 Slots |
| Max length space available for PCI slots | 333mm |
| I/O Ports | 2 x USB2.0 + 2 x USB3.0 + HD Audio / Mic + Fan Control |
| Height limit for CPU coolers | 185mm |
| Air Cooling System | Front : 1 x 20 or 1 x 23cm Fan (1 x 20cm LED Fan Included) Top : 2 x 12 or 1 x 14 or 1 x 20 or 1 x 23 cm Fan (1 x 20cm LED Fan Included) Bottom : 1 x 12 or 1 x 14cm Fan (Optional) Left Side : 2 x 12 or 2 x 14 or 1 x 20 or 1 x 23 cm Fan (Optional) Rear : 1 x 12 or 1 x 14cm Fan (1 x 14cm Fan Included) |
| Net Weight | 13.7Kg (G.W 16.1Kg) |
| EAN Code | 4713105952162 - Black Edition 4713105952179 - White Edition |

COOLING SYSTEM

| GT-S | [Rear] | [Front] | [Top] |
|-------------------------|-------------------|-------------------|-------------------|
| Black Edition | LED Fan | LED Fan | LED Fan |
| White Edition | LED Fan | LED Fan | LED Fan |
| Fan | 140 x 140 x 25 mm | 200 x 200 x 20 mm | 200 x 200 x 20 mm |
| Rated voltage | 12V | 12V | 12V |
| Operating Voltage Range | 10.8~13.2V | 10.8~13.2V | 10.8~13.2V |
| Starting voltage | 7V | 9V | 9V |
| Rated current | 0.14A+10%Max | 0.24A+10%Max | 0.24A+10%Max |
| Power consumption | 1.68W+10%Max | 2.88W+10%Max | 2.88W+10%Max |
| Speed | 1200+-10%RPM | 800+-200 RPM | 800+-200 RPM |
| Max AirFlow | 59.48CFM | 53.4CFM | 53.4CFM |
| Max Static Pressure | 0.95mm-H2O | 0.49mm-H2O | 0.49mm-H2O |
| Noise (dBA) | 26.3dBA | 27.6dBA | 27.6dBA |
| MTBF | 30,000 hours | 30,000 hours | 30,000 hours |