

SPECIFICATION

Model Name	V3X	V3X Advance
Case Type	Mid Tower	Mid Tower
Steel Thickness	0.5mm	0.5mm
Motherboards	ATX / Micro ATX / Mini ITX	ATX / Micro ATX / Mini ITX
Case Dimension	176 x 412 x 412mm (W x H x D, overall)	176 x 412 x 412mm (W x H x D, overall)
5.25" Drive Bays	3 (Exposed)	3 (Exposed)
3.5" FDD Drive Bays	1 (with 5.25" adapter)	1 (with 5.25" adapter)
3.5" Drive Bays	2 (Internal) + 1 (Side Mount) + 1 (5.25" Adapter)	2 (Internal) + 1 (Side Mount) + 1 (5.25" Adapter)
2.5" Drive Bays	2 (Side Mount)	2 (Side Mount)
Expansion Slots	7 Slots	7 Slots
GPU Clearance	320mm	320mm
I/O Ports	2 x USB2.0 / Audio(HD)+Mic	USB3.0 x 1 / USB2.0 x 1 / Audio(HD)+Mic
Height limit for CPU coolers	150mm	150mm
Air Cooling System	Front : 1 x 12cm Fan (Optional) Rear : 1 x 8cm Fan (Black Fan Included) Left Side : 2 x 12cm Fan (Optional)	Front : 1 x 12cm Fan (LED Fan Included) Rear : 1 x 8cm Fan (Black Fan Included) Left Side : 2 x 12cm Fan (Optional)
EAN Code	4710700957417 - Black Edition 4710700957455 - Devil Red Edition 4710700957448 - Evil Black Edition 4710700957424 - Evil Blue Edition 4710700957431 - Evil Green Edition	4710700957332 - Black Edition 4710700957400 - Devil Red Edition 4710700957394 - Evil Black Edition 4710700957349 - Evil Blue Edition 4710700957356 - Evil Green Edition

COOLING SYSTEM

V3X / V3X Advance	[Rear] - V3X / V3X Advance	[Front] - V3X Advance
Black Edition		LED Fan
Devil Red Edition		LED Fan
Evil Black Edition		LED Fan
Evil Blue Edition		LED Fan
Evil Green Edition		LED Fan
Fan	80 x 80 x 25 mm	120 x 120 x 25 mm
Rated Voltage	12V	12V
Operating Voltage Range	10.8~13.2V	6.0~13.2V
Starting Voltage	7V	6V
Rated Current	0.14A+-10%Max	0.25A+-10%Max
Power Consumption	2.16W+-10%Max	3.0W+-10%Max
Speed	1800+-10%RPM	1100+-10%RPM
Max AirFlow	28.4CFM	36.4CFM
Max Static Pressure	1.58mm-H2O	1.32mm-H2O
Noise (dBA)	21.6dBA	26.5dBA
MTBF	30,000 hours	20,000 hours