

SPECIFICATION

Model Name	Strike-X ONE	Strike-X ONE Advance
Case Type	Mid Tower	Mid Tower
Steel Thickness	0.5mm	0.5mm
Motherboards	Micro ATX / ATX	Micro ATX / ATX
Case Dimensions	190 x 485 x 460mm (W x H x D, overall)	190 x 485 x 460mm (W x H x D, overall)
Drive Bays	4 x 5.25" (Exposed) / 6 x 3.5" HDD or 2.5" HDD	4 x 5.25" (Exposed) / 6 x 3.5" HDD or 2.5" HDD
Expansion Slots	7 Slots	7 Slots
Max length space available for PCI slots	400mm	400mm
I/O Ports	2 x USB2.0 / Audio+Mic	2 x USB3.0 / Audio+Mic
Height limit for CPU coolers	158mm	158mm
Air Cooling System	Front : 1~3 12cm Fans - (w/Fan Adaptor) (Optional) Top : 2 x 12 Fan (Optional) Bottom : 1 x 12 or 14cm Fan (Optional) Left Side : 2 x 12 or 14cm Fans (Optional) Rear : 1 x 12cm Fan (Included) Inner front : 1~3 12cm Fans - (w/Fan adaptor) (Optional)	Front : 1~3 12cm Fans - (W/Fan Adaptor) / (1 x 12cm RED LED Fan Included) Top : 2 x 12 Fan (Optional) Bottom : 1 x 12 or 14cm Fan (Optional) Left Side : 2 x 12 or 14cm Fans (Optional) Rear : 1 x 12cm Fan (Included) Inner front : 1~3 12cm Fans - (W/Fan Adaptor) (Optional)
Net Weight	4.65 Kg (G.W 5.65Kg)	4.65 Kg (G.W 5.65Kg)
EAN Code	4710700958360 - Black Edition	4710700958377 - Black Edition

COOLING SYSTEM

Strike-X ONE / Strike-X ONE Advance	[Rear] Strike-X ONE / Strike-X ONE Advance	[Front] Strike-X ONE Advance
Black Edition		LED Fan
Fan	120 x 120 x 25mm	120 x 120 x 25mm
Rated voltage	12V	12V
Operating Voltage Range	6.0~13.2V	6.0~13.2V
Starting voltage	6V	6V
Rated current	0.12A+-10%Max	0.25A+-10%Max
Power consumption	1.44W+-10%Max	3.0W+-10%Max
Speed	1200+-10%RPM	1100+-10%RPM
Max AirFlow	36.4CFM	36.4CFM
Max Static Pressure	1.32mm-H2O	1.32mm-H2O
Noise (dBA)	26.5dBA	26.5dBA
MTBF	20,000 hours	20,000 hours