



STRIKE
X

1234567890

Advance

One

STRIKE X



STRIKE-X ONE ADVANCE

CASE

DESIGN CONCEPT



AS PART OF THE STRIKE-X FAMILY, THE STRIKE-X ONE AND STRIKE-X ONE ADVANCE ARE THE IDEAL BUDGET CASES FOR THOSE STRIKE-X SERIES LOVERS WITH TONS OF FEATURES BUT AT A MORE AFFORDABLE PRICE.

STRIKE-X ONE AND STRIKE-X ONE ADVANCE ARE DESIGNED WITH GAMERS IN MIND. LIKE THE REST OF THE FAMILY, THE FRONT PANEL CONSTITUTES A SYMBOLIC X SIGN WHICH CLEARLY IDENTIFIES ITSELF AS PART OF THE STRIKE-X FAMILY. THE DESIGN IS SIMPLE BUT YET CHARACTERISTIC. (FOR THE STRIKE-X ONE ADVANCE VERSION, THE CASE SUPPORTS 2 X USB3.0 PORTS WITH INTERNAL CONNECTION AND AN EXTRA 12CM COOLING FAN.)

WITH THE HDD CONVERTORS INCLUDED IN THIS CASE, USER CAN EASILY INSTALL UP TO 6X2.5" HDD OR 3.5" HDD, AND ALSO EACH CONVERTOR ACTS AS A FAN BRACKET FOR A 12CM FAN TO BE MOUNTED AT THE OPPOSITE SIDE OF THE HDD TO COOL THE HEAT THAT HDD GENERATES.

NOT ONLY THESE CONVERTORS CAN BE MOUNTED VERTICALLY TO THE FRONT OF THE CASE, THEY CAN ALSO BE MOUNTED TO THE INNER FRONT (FIRST OF THIS KIND IN THE MARKET) OF THE CASE SO THAT THE FAN/S ON THE CONVERTORS ARE CLOSER TO THE MOTHERBOARD WHERE THE COMPONENTS CAN BE COOLED MORE EFFICIENTLY.

FOR A BUDGET CASE, THIS IS THE OPPORTUNITY SIMPLY JUST TOO GOOD TO MISS.

TAKE A CLOSER LOOK TO FIND OUT MORE REASONS WHY YOU SHOULD BUY THIS CASE!



FEATURES



- All black chassis interior (0.5mm thickness)
- Supports Long VGA Cards up to 400mm
- Includes 1 x 12cm Black fan (Back)
- w/ Dust filter for PSU
- w/ 4 x ODD screw-less kit
- w/ 6 x 5 1/4" < 3 1/2" convertor brackets – can be used as fan adaptor, can install 3.5" HDDs and 2.5" HDDs and can be used to install floppy or card reader.
- w/ Cable Routing Management (pre-drilled holes on the MB plate)
- w/ Pre-drilled CPU holes for easy mounting and removable of CPU cooler
- w/ USB3.0 (internal) x 2 + Audio (HD) + Mic
- w/ 12cm RED Led fan (front)



STRIKE-X ONE ADVANCE

CASE

GALLERY





STRIKE-X ONE ADVANCE



CASE

SPECIFICATIONS

Case type	Mid Tower
Material	SPCC 0.5mm
Motherboard	Micro ATX / ATX
Case dimensions	440mm (H) x 180mm (W) x 475mm (D)
Drive bays	4 x 5.25" (Exposed) / 6 x 3.5" HDD or 2.5 HDD
Expansion slots	7
Max. length space available for PCI slots	400mm
I/O ports	2x USB3.0 or 2x USB2.0 / Audio+Mic



COOLING SYSTEM

	Front 120 x 120 x 25 mm 1 Quad RED LEDs" x 1		Back 120 x 120 x 25 mm x 1	
Rated Voltage	12V		12V	
Starting Voltage	<=6V(Power ON/OFF)		<=6V(Power ON/OFF)	
Power Consumption	1.2W		1.2W	
Rated Current	0.2A		0.2A	
Speed	1200		1200	
Air Flow	39 CMF-H2O		39 CMF-H2O	
Noise	23dBA		23dBA	
MTBF	20000 hours		20000 hours	




STRIKE-X ONE ADVANCE

CASE

AIR FLOW

Superb airflow - install up to 12 fans !!

1. Front - can install 1~3 12cm fans - (w/Fan adaptor) / (1 x 12cm RED LED fan included)
2. Top - 2 x 12 fan (optional)
3. Bottom - 1 x 12 or 14cm fan (optional)
4. Left Side - 2 x 12 or 14cm fans (optional)
5. Rear - 1 x 12cm fan (included)
6. Inner front - can install 1~3 12cm fans - (w/Fan adaptor) (optional)






STRIKE-X ONE ADVANCE

CASE

INSIDE



Dual fans on top panel to extract heat from chassis



Can install 1x12 cm fan at bottom of case



Fan can be mounted to the HDD adaptor to cool HDD



Tool-free for 5.25" bay



Can install 12 cm fan 1~3 pcs



Pre-drill pipe holes for water cooling



Pre-drilled holes for cable management



Can install 12 cm fan 1~3 pcs on front panel



USB 3.0 x 2



Sufficient depth of chassis for installing long cards



HDD can be mounted with adaptor



Install up to 2 x 12 or 14cm fans on side panel



Pre-drilled hole for easy access to CPU mounting bracket




FDD can be mounted with adaptor



STRIKE-X ONE ADVANCE

CASE

CLOSE UP



STRIKE X